

# Φ5MM WHITE ROUND LED

## A-503BU32W37C

### Features

- Round type
- White emitting color
- Low current operation
- Lead free, RoHS compliant

### Applications

- Indicator
- TV set
- Auto
- Monitor

### Ordering Information

Part Number	Emission Color	Lens Color	Bin Code	Luminous Intensity IV (mcd) (IF=20mA)		
				Min.	Typ.	Max.
A-503BU32W37C	White	Water Clear	S	17550	21938	26325
			T	26326	32908	39489
			U	39490	49363	59235

**Maximum Ratings**

Parameter	Symbol	Value	Unit
Operating temperature	T <sub>OP</sub>	-35 ~ 85	°C
Storage temperature	T <sub>STG</sub>	-35 ~ 85	°C
Forward current (T <sub>A</sub> =25 °C)	I <sub>F</sub>	30	mA per seg
Peak forward current (T <sub>A</sub> =25 °C) * <sup>1</sup>	I <sub>PF</sub>	120	mA per seg
Reverse voltage (T <sub>A</sub> =25 °C)	V <sub>R</sub>	5	V per seg
Power consumption (T <sub>A</sub> =25 °C)	P	80	mW per seg

\*1 at 1/10 Duty Cycle






**Electrical / Optical Characteristics (1)**(T<sub>A</sub> = 25 °C)

Parameter	Symbol	Value	Unit
Color Temperature IF = 20mA	(Min.) T <sub>C</sub>	4600	K
Color Temperature IF = 20mA	(Max.) T <sub>C</sub>	15000	K
Color coordinates IF = 20mA	(Min.) X Axis	0.264	-
Color coordinates IF = 20mA	(Max.) X Axis	0.361	-
Color coordinates IF = 20mA	(Min.) Y Axis	0.248	-
Color coordinates IF = 20mA	(Max.) Y Axis	0.385	-
Spectral bandwidth at 50% IF = 20mA	(Typ.) Δλ	30	nm
Viewing angle at 50% IF = 20mA	(Typ.) 2θ <sub>1/2</sub>	13	degree
Forward voltage IF = 20mA	(Min.) V <sub>F</sub>	2.8	V
	(Typ.) V <sub>F</sub>	3.2	V
	(Max.) V <sub>F</sub>	3.6	V
Reverse current V <sub>R</sub> = 5V	(Max.) I <sub>R</sub>	10	μA
Optical efficiency IF = 20mA	(Typ.) η <sub>OPT</sub>	-	lm/W


**Luminous Intensity Bin Groups**(T<sub>A</sub> = 25 °C & I<sub>F</sub> = 20 mA)

Bin Code	Luminous Intensity I <sub>v</sub> (mcd)		
	Min.	Typ.	Max.
S	17550	21938	26325
T	26326	32908	39489
U	39490	49363	59235

Electrical/Optical Charateristic (2)



## Package Outline Dimensions



## Notes:

1. All dimensions are in millimeters. Tolerance is +/-0.25 unless otherwise noted.
2. The specifications, characteristics and technical data described in the datasheet are subject to change without prior notice.

## Display Soldering Conditions

The recommended conditions for soldering are as follows. Because the component is made with epoxy resin, the units are susceptible to heat. Therefore, the preheating and soldering temperatures should be kept as low as possible to avoid damage.


### 1 . Manual Soldering Conditions(with 1.5mm Iron tip )

Iron Tip Temperature: 350°C Max, Time: 3s Max

Position: The iron should be situated at least 2mm away from the root of the leads.

### 2 . Through the Wave Soldering Conditions

Wave Soldering Profile For Lead-free Through-hole LED



### 3 . Soldering General Notes:

- TOPLITE recommend manual soldering to be used only for repair and rework purposes. The soldering iron should not exceed 30W in power. The tip of the soldering iron should not touch the reflector case to avoid heat-damage.
- Maintain the pre-heat and peak temperatures with dip units as low as possible and the times as short as is feasible, since the products are susceptible to heat during flow soldering.
- After soldering, allow at least three minutes for the component to cool to room temperature before further operations.
- If components will undergo multiple soldering processes, or other processes where the components may be subjected to intense heat, please check with TOPLITE for compatibility.