

SPECIFICATIONS

Dot matrix Display **点阵产品规格书**

TOPLITE



MODEL: TOP-CC-1067ASO

上海鼎晖科技股份有限公司
SHANGHAI TOPLITE TECHNOLOGY CO.,LTD.

www.ledtoplight.com.cn
www.ledtoplite.com



TECHNICAL DATA SHEET

TOP-CA-1067BPA FOR 1.1 inch (27mm) matrix height

1 / 6

1. FEATURES

- ※ Low power requirement,
- ※ Solid state reliability.
- ※ Wide viewing angle.
- ※ Easy mounting on P.C. boards.
- ※ RoHS compliant.

2. DESCRIPTION

- ※ **TOP-CC-1067ASO** is a **1.1 inch (27mm) matrix height**
- ※ This device is made with white dots and black surface.

3. APPLICATION

- ※ Digital readout display.
- ※ Instrument panels.
- ※ Elevator.






PART NO.	SIZE	CHIP EMITTED COLOR	FACE COLOR
TOPLIGHT-CC-1067ASO	1.1 inch (27mm) matrix height	Amber	Black

TECHNICAL DATA SHEET

TOP-CA-1067BPA FOR 1.1 inch (27mm) matrix height

2 / 6

4. PACKAGE DIMENSIONS & CIRCUIT DIAGRAM



**TECHNICAL DATA SHEET**

TOP-CA-1067BPA FOR 1.1 inch (27mm) matrix height

3 / 6

5. ELECTRICAL/OPTICAL CHARACTERISTIC**5-1. ABSOLUTE MAXIMUM RATINGS (Ta=25°C)**

PARAMETER	SYMBOL	VALUE	UNIT
Reverse Voltage	V_R	5	V/dot
Forward Current	I_F	30	mA/dot
Peak Forward Current (1/10 Duty Cycle)	I_{PEAK}	120	mA/dot
Power Dissipation	P_D	80	mW/dot
Operating Temperature Range	T_A	- 25 ~ + 85	°C
Storage Temperature Range	T_{STG}	- 30 ~ + 85	°C
Solder Temperature	T_{sol}	260/3	°C/s

5-2. ELECTRICAL/OPTICAL CHARACTERISTICS (Ta=25°C)






PARAMETER	SYMBOL		MIN.	TYP.	MAX.	UNIT	TEST CONDITIONS
Luminous Intensity	I_V	T	26326	32907.5	39489	ucd	$I_F=10mA$
		U	39490	49362.5	59235		
		V	59236	74045	88854		
Forward Voltage	V_F		1.80	2.10	2.40	v/dot	$I_F=20mA$
Chromatographer	λ_p		-	605	-	nm	$I_F=20mA$
Spectral Line Half-Width	$\Delta \lambda$		-	20	-	nm	$I_F=20mA$
Reverse Current	I_R		-	-	20	uA	$V_R=5v$

TECHNICAL DATA SHEET

TOP-CA-1067BPA FOR 1.1 inch (27mm) matrix height

4 / 6

5-3. ELECTRICAL/OPTICAL CHARACTERISTIC CURVES



**TECHNICAL DATA SHEET**

TOP-CA-1067BPA FOR 1.1 inch (27mm) matrix height

5 / 6

6. QUALITY CONTROL AND ASSURANCE

CLASSIFICATION	TEST ITEM	TEST CONDITION
ENDUTRANCE TEST	OPERATION LIFE	Ta=under room temperature If=12mA-25mA per segment or Ip=80mA/duty=1/8,Pw=1.25mS Ip=160mA/duty=1/16,Pw=1.mS(DOT) Test time=1000HRS(-24HRS+72HRS)
	MOISTURE	Ta=65℃±5℃ RH=90-95% Test time=240HRS±2HRS
	HIGH TEMPERATURE HIGH HUMIDITY REVERSE BIAS	Ta=65℃±5℃ RH=90-95% VR=5V Test time=500hrs(-24HRS+48HRS)
	HIGH TEMPERATURE STORAGE	To evaluate device's durability for long term storage in high temperature Ta=85℃±5℃ Test time=1000HRS(-24HRS+72HRS)
	LOW TEMPERATURE STORAGE	Ta=-35℃±5℃ Test time=1000HRS(-24HRS+72HRS)
ENVIRONMENTAL TEST	TEMPERATURE CYCLING	Ta=85℃~25℃~-35℃ time=30min 5min 30min 5min Cycle test:10cycles
	THERMAL SHOCK	Ta=85℃±5℃~-35℃±5℃ time=10min 10min Cycle test:10cycles
	SOLOER RESISTANCE	T.sol=260℃±5℃ time=10±1sec
	SOLOER ABILITY	T.sol=230℃±5℃ time=5±1sec

TECHNICAL DATA SHEET

TOP-CA-1067BPA FOR 1.1 inch (27mm) matrix height

6 / 6

7. SOLDERING CONDITIONS

The recommended conditions for soldering are as follows.


Because the component is made with epoxy resin, the units are susceptible to heat. Therefore, the preheating and soldering temperatures should be kept as low as possible to avoid damage.

7-1. Manual Soldering Conditions(with 1.5mm Iron tip).

Iron Tip Temperature: 350°C Max, Time: 3s Max.

Position: The iron should be situated at least 2mm away from the root of the leads.

7-2. Through the Wave Soldering Conditions Wave Soldering Profile For Lead-free Through-hole LED.



7-3. Soldering General Notes:

- Recommend manual soldering to be used only for repair and rework purposes. The soldering iron should not exceed 30W in power. The tip of the soldering iron should not touch the reflector case to avoid heat-damage.
- Maintain the pre-heat and peak temperatures with dip units as low as possible and the times as short as is feasible, since the products are susceptible to heat during flow soldering.
- After soldering, least three minutes for the component to cool to room temperature before further operations.
- If components will undergo multiple soldering processes, or other processes where the components may be subjected to intense heat, please check with for compatibility.