

# SPECIFICATIONS

LED Symbol 指示符产品规格书

TOPLITE



MODEL: TOP-R3006ZYG

上海鼎晖科技股份有限公司

SHANGHAI TOPLITE TECHNOLOGY CO.,LTD.

[www.ledtoplight.com.cn](http://www.ledtoplight.com.cn)

[www.ledtoplite.com](http://www.ledtoplite.com)



## TECHNICAL DATA SHEET TOP-R3006

1 / 6

### 1. FEATURES

- ※ Low power requirement,
- ※ Solid state reliability.
- ※ Square emitting surface.
- ※ Easy mounting on P.C. boards.
- ※ RoHS compliant.

### 2. DESCRIPTION

- ※ The TOPLITE TOP-R3006ZYG is a round light emitting surface of the light bar.
- ※ This device is made with red segments and black surface..

### 3. APPLICATION

- ※ Audio equipment.
- ※ Instrument panels.
- ※ Elevator.


PART NO.	SIZE	CHIP EMITTED COLOR	FACE COLOR
TOP-R3006ZYG	Φ 30.8mm	Yellow Green	White

## TECHNICAL DATA SHEET

### TOP-R3006

2 / 6

#### 4. PACKAGEDIMENSIONS& CIRCUIT DIAGRAM



**TECHNICAL DATA SHEET**  
**TOP-R3006**

3 / 6

**5. ELECTRICAL/OPTICAL CHARACTERISTIC****5-1. ABSOLUTE MAXIMUM RATINGS(Ta=25℃)**

PARAMETER	SYMBOL	VALUE	UNIT
Reverse Voltage	$V_R$	5	V/dot
Forward Current	$I_F$	30	mA/dot
Peak Forward Current (1/10 Duty Cycle)	$I_{PEAK}$	120	mA/dot
Power Dissipation	$P_D$	80	mW/dot
Operating Temperature Range	$T_A$	- 25 ~ + 85	℃
Storage Temperature Range	$T_{STG}$	- 30 ~ + 85	℃
Solder Temperature	$T_{sol}$	260/3	℃/s

**5-2. ELECTRICAL/OPTICAL CHARACTERISTICS(Ta=25℃)**






PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITIONS
Luminous Intensity	$I_V$	—	—	—	ucd	$I_F=10mA$
Forward Voltage	$V_F$	1.90	2.10	2.50	v/dot	$I_F=20mA$
Chromatographer	$\lambda_p$	—	570	—	nm	$I_F=20mA$
Spectral Line Half-Width	$\Delta \lambda$	—	20	—	nm	$I_F=20mA$
Reverse Current	$I_R$	—	—	20	uA	$V_R=5v$

## TECHNICAL DATA SHEET

### TOP-R3006

4 / 6

### 5-3. ELECTRICAL/OPTICAL CHARACTERISTIC CURVES



# **TECHNICAL DATA SHEET** **TOP-R3006**

5 / 6

## **6. QUALITY CONTROL AND ASSURANCE**

CLASSIFICATION	TEST ITEM	TEST CONDITION
ENDUTRANCE TEST	OPERATION LIFE	Ta=under room temperature If=12mA-25mA per segment or Ip=80mA/duty=1/8,Pw=1.25mS Ip=160mA/duty=1/16,Pw=1.mS(DOT) Test time=1000HRS(-24HRS+72HRS)
	MOISTURE	Ta=65℃±5℃ RH=90-95% Test time=240HRS±2HRS
	HIGH TEMPERATURE HIGH HUMIDITY REVERSE BIAS	Ta=65℃±5℃ RH=90-95% VR=5V Test time=500hrs(-24HRS+48HRS)
	HIGH TEMPERATURE STORAGE	To evaluate device's durability for long term storage in hightemperature Ta=85℃±5℃ Test time=1000HRS(-24HRS+72HRS)
	LOW TEMPERATURE STORAGE	Ta=-35℃±5℃ Test time=1000HRS(-24HRS+72HRS)
ENVIRONMENTAL TEST	TEMPERATURE CYCLING	Ta=85℃～25℃～-35℃ time=30min 5min 30min 5min Cycle test:10cycles
	THERMAL SHOCK	Ta=85℃±5℃～-35℃±5℃ time=10min 10min Cycle test:10cycles
	SOLOER RESISTANCE	T.sol=260℃±5℃ time=10±1sec
	SOLOER ABILITY	T.sol=230℃±5℃ time=5±1sec

## TECHNICAL DATA SHEET

### TOP-R3006

6 / 6

## 7. SOLDERING CONDITIONS

The recommended conditions for soldering are as follows.


Because the component is made with epoxy resin, the units are susceptible to heat. Therefore, the preheating and soldering temperatures should be kept as low as possible to avoid damage.

### 7-1. Manual Soldering Conditions (with 1.5mm Iron tip) .

Iron Tip Temperature: 350°C Max, Time: 3s Max.

Position: The iron should be situated at least 2mm away from the root of the leads.

### 7-2. Through the Wave Soldering Conditions Wave Soldering Profile For Lead-free Through-hole LED.



### 7-3. Soldering General Notes:

- Recommend manual soldering to be used only for repair and rework purposes. The soldering iron should not exceed 30W in power. The tip of the soldering iron should not touch the reflector case to avoid heat-damage.
- Maintain the pre-heat and peak temperatures with dip units as low as possible and the times as short as is feasible, since the products are susceptible to heat during flow soldering.
- After soldering, least three minutes for the component to cool to room temperature before further operations.
- If components will undergo multiple soldering processes, or other processes where the components may be subjected to intense heat, please check with for compatibility.